

Congratulations

You have just purchased the most advanced power meter technology available. You will soon be riding with Pioneer Power! In order to ensure the fastest installation of the crank arm sensors and safest delivery of your new power meter we have provided this Birth Certificate. Please fill out the form completely and return with your crank shipment.

Thank you, Pioneer Cycle Sports Team

On-Line Registration / Free Shipping Instructions

- 1. Visit: www.powerisking.com/kit
- 2. Register and complete the on-line Birth Certificate
- 3. Print the completed Birth Certificate and insert a copy in the return shipping box with your crankset and sensor(s).
- 4. Print the pre-paid 2-Day shipping label and affix to the return shipment box.
- 5. Pack your crankset or crank arm in the return shipment box .
- 6. Ship crankset, sensors, and Birth Certificate to Pioneer Cycle Installation Center

Manual Registration / Consumer Paid Shipping Instructions

- 1. Fill out the information requested on the back of this Birth Certificate
- 2. Insert the completed Birth Certificate in the return shipping box with your crankset and sensor(s).
- 3. Pack your crank set or crank arm in the return shipment box .
- 4. Ship crankset, sensors, and this Birth Certificate to Pioneer Cycle Installation Center

Ship to: Pioneer Cycle Technology 19148 Van Ness Avenue Torrance, CA 90501

IMPORTANT NOTICES:

- 1. Dealer or consumer should ensure that the sensors will have sufficient frame clearance and will not come into contact with the bicycle frame. This must be performed BEFORE sending the crank/arm in to Pioneer for installation.
- 2. The Left Arm Sensor will add an additional 10mm to the inside depth of your left crank arm. Please consider this additional depth and the possibility of contact with your frame. Pioneer is NOT RESPONSIBLE for any damage to the frame.
- 3. Installation requires the use of epoxy adhesive. In the event of removal of the sensors, the sensor cannot be reused and there may be some cosmetic or residual damage to the crank surface.
- 4. Pioneer Power Meter Sensors are only compatible with specific cranks. If it is determined that the sensor is not compatible with the crank received, the crank will be returned without the sensors attached.
- 5. Only Pioneer Power Meter components are covered by factory warranty.

Notice regarding filling out this sheet and transporting the crank. Pioneer will install the Power Meter System to the provided crank/arm based on the information provided, please ensure that all information is accurate and complete. Please remove any accessories and thoroughly clean your crank/arm of any mud, dirt, or grease before shipment.

For more installation support please visit: www.POWERisKING.com/kit



POWER METER BIRTH CERTIFICATE

BICYCLE INFORMATION

BIKE FRAME		Brand: Model Name: Some Frames and Bottom Brackets are	Year: Frame Size: e not compatible with the pedaling monitor sys	stem. Please confirm before ordering.
STEP	PIONEER KIT PURCHASED (Check Kit Purchased)			
1	Dual Leg	SBT-PM9100C	Left Leg SBT-PMLTC	Right Leg SBT-PMRTC
	Dual Leg	SGY-PM9100C	Left Leg SGY-PMLTC	Right Leg SGY-PMRTC
STEP	SBT Kit Comp	patibility (Check One) SBT K	Kits Only Compatible With New	Dura-Ace and Ultegra
2	SBT-Kits	Dual Leg Crankset SBT-PM9100C	Left Crank Arm Only SBT-PMLTC	Drive Side Crank Arm Only SBT-PMRTC
	Compatible Crank / Arm	Dura-Ace FC-R9100	Dura-Ace FC-R9100 - Left	Dura-Ace FC-R9100 - Right Ultegra FC-R8000 - Right
STEP	SGY Kit Compatibility (Check One)			
2	SGY-Kits	Dual Leg Crankset SGY-PM9100C	Left Crank Arm Only SGY-PMLTC	Drive Side Crank Arm Only SGY-PMRTC
	Compatible Crank / Arm	 Dura-Ace FC-R9100 Dura-Ace FC-9000 Ultegra FC-R8000 Ultegra FC-6800 Campagnolo Potenza II 	 Dura-Ace FC-R9100 - Left Dura-Ace FC-9000 - Left Ultegra FC-R8000 - Left Ultegra FC-6800 - Left Shimano 105 - Left Campagnolo Potenza II - Left Cannondale - Left Hollowgra Cannondale - Left Hollowgra Shimano XTR-Trail FC-M9020 Shimano XT FC-M8000 - Left 	m SiSL2
STEP	ARM TYPE & CHAIN RING TYPE (Check One)			
3	Crank / Arm Configuration	DUAL LEG / RIGHT SIDE Chain F	Ring /	LEFT LEG Arm Length
STEP	FRAME CLEARANCE			
4	Please The distance between the frame and crank was checked to ensure that the Power Meter System is compatible with the frame. Left crank arm sensors require a minimum of 10mm clearance from the inside of the arm to the chainstay.			
STEP	PERSONAL INFORMATION			
5	First name Last name			
	Mailing address (Number and street or rural route) Apartment/Suite number			
	City, village, or post office		State	ZIP code
	E-Mail Address:			Contact phone:
	Customer Signa	iture:		Date: